



# CONTROL DEVICES EMERGENCY STOP AND RESET PUSHBUTTONS

- Easy mounting
- Error-free connection
- Suitable for applications in the safety technology

## FAST AND ERROR-FREE WIRING WITH STANDARD CABLES

The **EMERGENCY STOP** and **RESET** buttons from Murrelektronik can be integrated very easily in electronic installations

These control and monitoring devices can be connected via preconfigured M12 cables (4-, 5-, or 8-pole). A time-saving solution excluding the risk of faulty wirings. The 'Plug & Play' feature makes integrating the control devices in machines and systems faster.

### 42 mm variants



#### E-Stop button

- With M12 connection
- 4-, 5-, or 8-pole variants

*Page 2.5.1*



#### R-Button

- With M12 connection
- 4- or 8-pole variants

*Page 2.5.1*

### 72 mm variants



#### E-Stop button

- With M12 connection
- 4-, 5-, or 8-pole variants
- With / without protective collar

*Page 2.5.1*

Control devices			Art-No.
	E-Stop 42 2NC M12(4) M12 (4-pole)	Emergency-Stop button 2 NC (positively-opening)	69000
	E-Stop 42 2NC M12(5) M12 (5-pole)	Emergency-Stop button 2 NC (positively-opening)	69001
	E-Stop 42 2NC L M12(8) M12 (8-pole)	Emergency-Stop button 2 NC (positively-opening) LED-Ring can be lit	69002
	E-Stop / R-B 42 2NC 1NO M12(8) M12 (8-pole)	Emergency-Stop button 2 NC (positively-opening) 1 button (1 NO contact) Flat lens, transparent clear, red, yellow, green, blue	69003
	E-Stop / R-B 42 2NC 1NO L M12(8) M12 (8-pole)	Emergency-Stop button 2 NC (positively-opening) 1 button can be lit (1 NO contact) Flat lens, transparent clear, red, yellow, green, blue	69004
	R-Button / 42 1NO M12(4) M12 (4-pole)	1 button (1 NO contact) Flat lens, transparent clear, red, yellow, green, blue	69010
	R-Button / 42 1NO L M12(4) M12 (4-pole)	1 button can be lit (1 NO contact) Flat lens, transparent clear, red, yellow, green, blue	69013
	R-Button / 42 2NO M12(4) M12 (4-pole)	2 buttons (each 1 NO contact) Flat lens, transparent clear, red, yellow, green, blue	69011
	R-Button / 42 2NO L M12(8) M12 (8-pole)	2 buttons can be lit (each 1 NO contact) Flat lens, transparent clear, red, yellow, green, blue	69012
	E-Stop 72 2NC M12(4) M12 (4-pole)	Emergency-Stop button 2 NC (positively-opening)	55550
	E-Stop 72 2NC M12(5) M12 (5-pole)	Emergency-Stop button 2 NC (positively-opening)	69041
	E-Stop 72 2NC L M12(8) M12 (8-pole)	Emergency-Stop button 2 NC (positively-opening) LED-Ring can be lit	69043
	E-Stop 72P 2NC M12(4) M12 (4-pole)	Emergency-Stop button 2 NC (positively-opening) with protection shroud	69040
	E-Stop 72P 2NC M12(5) M12 (5-pole)	Emergency-Stop button 2 NC (positively-opening) with protection shroud	69042

## CONTROL DEVICES

Accessories control devices			Art-No.
	<b>T-coupler (SlimLine) M12 - M12</b> Male straight - female/male straight	for 8-pole Emergency-Stop button	<b>7030-42622-0000000</b>

Control devices