

LIGHTING ELEMENTS MAXIMUM FLEXIBILITY

- High light yield
- Long life
- Plug-in solutions

DISTINCT SIGNALS AND PERFECT ILLUMINATION IN DAYLIGHT QUALITY

Modlight Pro LED signal towers

The signal towers are characterized by maximum flexibility in color selection and color composition. The elements of the signal towers with diameters of 50 and 70 millimeters are connected by bayonet locks, making for easy and quick assembly. The signal towers can be flexibly mounted.

Modlight Illumix LED machine light

The machine lights of the Modlight Illumix series ensure optimal illumination of machines and systems based on maintenance-free and durable LED technology in daylight quality. Rotatable mounting brackets provide flexibility in attaching the lights.

Signal lights



Modlight50 Pro / Modlight70 Pro

- 50/70 mm
- Connecting elements
- Buzzer modules
- LED modules

Page 2.4.1



Sets – Modlight30 / Modlight50 Pro / Modlight70 Pro

- 30/50/70 mm
- LED signal towers

Page 2.4.2



Comlight57

- 57 mm
- Single lights
- LED

Page 2.4.3

Machine lights




Modlight Illumix Slim Line

- Machine light (LED)
- Degree of protection IP54

Modlight Illumix Classic Line

- Machine light (LED)
- Degree of protection IP67

Page 2.4.5



Modlight Illumix Xtreme

- Machine light (LED)
- Degree of protection IP69K

Page 2.4.6

Connection modules			Art-No.
	Base for floor mount Modlight50 Pro	Spring clamp terminals cURus	4000-76050-1100002
	Base for floor mount Modlight70 Pro	Spring clamp terminals cURus	4000-76070-1100002
	Basic for tube mounting Modlight50 Pro	Spring clamp terminals cURus	4000-76050-1100003
	Basic for tube mounting Modlight70 Pro	Spring clamp terminals cURus	4000-76070-1100003
	Basic Modlight70 Pro	M12 (8-pole), down	4000-76070-1300002
	Basic Modlight70 Pro	M12 (8-pole), sideways	4000-76070-1400002
	Basic with magnet base Modlight70 Pro	M12 (8-pole), sideways	4000-76070-1500002
Buzzer modules			Art-No.
	Buzzer module Modlight50 Pro		4000-76050-1100004
	Buzzer module Modlight70 Pro		4000-76070-1100004
LED modules			Art-No.
	LED module Modlight50 Pro	red	4000-76050-1011000
	LED module Modlight70 Pro	red	4000-76070-1011000
	LED module Modlight50 Pro	yellow	4000-76050-1012000
	LED module Modlight70 Pro	yellow	4000-76070-1012000






LIGHTING ELEMENTS

LED modules			Art-No.
	LED module Modlight50 Pro	green	4000-76050-1013000
	LED module Modlight70 Pro	green	4000-76070-1013000
	LED module Modlight50 Pro	blue	4000-76050-1014000
	LED module Modlight70 Pro	blue	4000-76070-1014000
	LED module Modlight50 Pro	clear	4000-76050-1015000
	LED module Modlight70 Pro	clear	4000-76070-1015000
Sets			Art-No.
	Modlight30 (green/yellow/red)		
	Connection module + LED modules	Connection cable L = 300 mm	4000-75324-5310000
	Connection module + LED modules	Connection M12 (on bottom)	4000-75330-5310000
	Modlight50 Pro (green/yellow/red)		
	Basic + LED modules		4000-76501-5310000
	Basic, buzzer + LED modules		4000-76502-5310000
	Modlight70 Pro (green/yellow/red)		
	Basic + LED modules + M12 (down)		4000-76704-5310000
	Basic, buzzer + LED modules + M12 (down)		4000-76705-5310000
	Modlight70 Pro (green/yellow/red)		
	Basic + LED modules + M12 (side)		4000-76712-5310000
	Basic, buzzer + LED modules + M12 (side)		4000-76713-5310000

Compact status lights			Art-No.
	Comilight57		
	red	Spring clamp terminal connection	4000-75057-1111000
	red	Connection M12 (on bottom)	4000-75057-1311000
	Comilight57		
	yellow	Spring clamp terminal connection	4000-75057-1112000
	yellow	Connection M12 (on bottom)	4000-75057-1312000
	Comilight57		
	green	Spring clamp terminal connection	4000-75057-1113000
	green	Connection M12 (on bottom)	4000-75057-1313000
	Comilight57		
	blue	Spring clamp terminal connection	4000-75057-1114000
	blue	Connection M12 (on bottom)	4000-75057-1314000
	Comilight57		
	clear	Spring clamp terminal connection	4000-75057-1115000
	clear	Connection M12 (on bottom)	4000-75057-1315000

LIGHTING ELEMENTS

Accessories Modlight30			Art-No.
	Adapter for wall assembly		4000-75030-0000903
Accessories Modlight50/70 Pro			Art-No.
	Bottom adapter for tube mounting	for Modlight50/70 Pro	4000-76070-0000901
	Adapter for tube/wall mounting	for Modlight50/70 Pro	4000-76070-0000902
	Adapter for wall assembly	for Modlight70 Pro	4000-76070-0000903
	Adapter for wall assembly Cable outlet (on the bottom)	for Modlight70 Pro	4000-75070-0000904
	Aluminum tube 300 mm	for Modlight50/70 Pro	4000-76070-0000913
	800 mm	for Modlight50/70 Pro	4000-76070-0000918
	Magnet base with M16 x 1.5 gland	Sideways cable entry point for Modlight50/70 Pro	4000-75070-0000920
	Magnet base with M12 flange plug connector (8-pole)	Sideways connection for Modlight50/70 Pro	4000-75070-0000921

Accessories Modlight50/70 Pro			Art-No.
	Mounting adapter for strain relief	bottom or side exit	4000-75070-0000922
	Label plate transparent	for Modlight50 Pro	4000-76050-0000923
	transparent	for Modlight70 Pro	4000-76070-0000923
LED machine lights			Art-No.
	Modlight Illumix Slim Line 4 W - 24 V DC Connection M8	IP54 cULus	4000-75800-1715004
	8 W - 24 V DC Connection M8	IP54 cULus	4000-75800-1715008
	16 W - 24 V DC Connection M8	IP54 cULus	4000-75800-1715016
	24 W - 24 V DC Connection M8	IP54 cULus	4000-75800-1715024
	32 W - 24 V DC Connection M8	IP54 cULus	4000-75800-1715032
	Modlight Illumix Slim Line C 4 W - 24 V DC Connection M8 expandability	IP54 cULus	4000-75900-1715004
	8 W - 24 V DC Connection M8 expandability	IP54 cULus	4000-75900-1715008
	16 W - 24 V DC Connection M8 expandability	IP54 cULus	4000-75900-1715016
	24 W - 24 V DC Connection M8 expandability	IP54 cULus	4000-75900-1715024
	32 W - 24 V DC Connection M8 expandability	IP54 cULus	4000-75900-1715032
	Modlight Illumix Classic Line 6 W - 24 V DC Connection M12	IP67 cULus	4000-75801-1415006
	12 W - 24 V DC Connection M12	IP67 cULus	4000-75801-1415012
	18 W - 24 V DC Connection M12	IP67 cULus	4000-75801-1415018
	24 W - 24 V DC Connection M12	IP67 cULus	4000-75801-1415024

LIGHTING ELEMENTS

LED machine lights			Art-No.
	<p>Modlight Illumix Classic Line C</p> <p>6 W - 24 V DC Connection M12 expandability</p> <p>12 W - 24 V DC Connection M12 expandability</p> <p>18 W - 24 V DC Connection M12 expandability</p> <p>24 W - 24 V DC Connection M12 expandability</p>	<p>IP67 cULus</p> <p>IP67 cULus</p> <p>IP67 cULus</p> <p>IP67 cULus</p>	<p>4000-75901-1415006</p> <p>4000-75901-1415012</p> <p>4000-75901-1415018</p> <p>4000-75901-1415024</p>
	<p>Modlight Illumix Xtreme</p> <p>27 W - 24 V DC Connection M12</p>	<p>IP69K cULus</p>	<p>4000-75827-1315000</p>
	<p>Modlight Illumix Xtreme</p> <p>Joint coupling</p>		<p>4000-75800-0000900</p>